Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

- (canceled)
- (currently amended) The golf ball of claim 1, A golf ball comprising:

an inner core having a compression of less than about 65;

at least one outer core layer surrounding the inner core having a specific gravity greater than or equal to a specific gravity of the inner core; and

a cover surrounding the outer core laver:

wherein the inner core hardness is about 78 Shore C and the outer core hardness is greater than about 90 Shore C; and

wherein the inner core has a diameter of from about 1.4 inches to about 1.5 inches and the outer core has a thickness of from about 0.05 inches up to about 0.1 inches.

- 3-9. (canceled)
- (currently amended) The golf ball of claim + 2, wherein the cover layer comprises
 polyurea or polyurethane.
- 11. (currently amended) The golf ball of claim + 2, further comprising a moisture barrier layer disposed between the outer core layer and the cover layer, wherein the moisture barrier layer comprises a moisture vapor transmission rate that is less than a moisture vapor transmission rate of the cover layer.
- (original) The golf ball of claim 11, wherein the moisture barrier layer has a specific gravity of from about 1 to about 2, and a thickness of less than about 0.03 inches.
- (original) The golf ball of claim 11, wherein the moisture barrier layer comprises a styrene block copolymer and aluminum flake.

Appl. No.: 10/773.906

Art Unit: 3711 Docket No.: B03-70 Response dated February 20, 2007

Reply to Office Action of November 20, 2006

14-22. (canceled)

23. (original) A golf ball comprising:

a multi-layer core comprising:

an inner core having a Shore C hardness less than about 80 and a compression of less than about 70; and

at least one outer core layer having a Shore C hardness of greater than about 80,

an amount of zinc diacrylate of greater than about 35 pph; and

a cover layer having a Shore D hardness of less than about 65:

wherein at least one outer core layer has a moisture vapor transmission rate that is lower than that of the cover layer, and the multi-layer core has a diameter of greater than about 1.58 inches.

- 24. (original) The golf ball of claim 23, wherein the outer core layer has a Shore C hardness of greater than about 90.
- 25. (original) The golf ball of claim 24, wherein the zinc diacrylate level in the outer core layer is greater than about 40 pph.
- 26. (original) The golf ball of claim 24, wherein the multi-layer core diameter is greater than about 1.6 inches.
- 27. (original) The golf ball of claim 24, wherein the inner core comprises about 100 pph of a polybutadiene rubber, greater than about 25 pph of a zinc diacrylate, greater than about 0.5 pph of an organic peroxide and a sufficient amount of filler to produce the inner core specific gravity, the outer core comprises about 100 pph of a polybutadiene rubber. greater than about 0.6 pph of an organic peroxide, a sufficient amount of filler to produce the outer core specific gravity, and the cover layer comprises polyurea or polyurethane.

28. (canceled) Appl. No.: 10/773,906
Art Unit: 3711 Docket No.: B03-70
Response dated February 20, 2007
Reply to Office Action of November 20, 2006

29. (canceled)

(previously presented) A golf ball comprising:

an inner core having a compression of less than about 65;

at least one outer core layer surrounding the inner core and having a hardness of at least

80 Shore C and a specific gravity greater than or equal to a specific gravity of the inner

core; and

a cover surrounding the outer core layer;

wherein the inner core has a hardness less than a hardness of the outer core, and

wherein the cover layer comprises polyurea or polyurethane.

31. (previously presented) The golf ball of claim 30, wherein the inner core has a diameter of from about 1.4 inches to about 1.5 inches and the outer core has a thickness of from about 0.05

inches up to about 0.1 inches.

32. (previously presented) The golf ball of claim 30, wherein the cover layer has a thickness

of from about 0.03 inches to about 0.04 inches.

33. (previously presented) The golf ball of claim 30, wherein the inner core has a

compression of less than about 50.

34. (previously presented) The golf ball of claim 30, wherein the outer core layer has a

specific gravity of at least 1.1.

35. (previously presented) The golf ball of claim 30, wherein the golf ball further comprises a

moisture barrier layer disposed between the outer core layer and the cover layer, wherein the moisture barrier layer comprises a moisture vapor transmission rate that is less than a moisture

vapor transmission rate of the cover layer.

Page 4 of 7

Appl. No.: 10/773,906 Art Unit: 3711 Docket No.: B03-70 Response dated February 20, 2007 Reply to Office Action of November 20, 2006

- 36. (previously presented) The golf ball of claim 35, wherein the moisture barrier layer has a specific gravity of from about 1 to about 2.
- 37. (previously presented) The golf ball of claim 36, wherein the moisture barrier layer has a thickness of less than about 0.03 inches.
- (previously presented) The golf ball of claim 35, wherein the moisture barrier layer comprises a styerene block copolymer and aluminum flake.